

Norfield



norfield.com

1-800-824-6242

1700 AUTOMATIC HINGE JAMB ROUTER

HIGH PRODUCTION HINGE JAMB ROUTER



Quickly change hinge mortise locations without tools



Quick change turret stop system for various hinge backsets and sizes



Automatic routing for both 5/8" and 1/4" radius hinge corners



Dual palm pads keep operator's hands away from moving parts, improving safety.

Throughput Rate

4-5
jamb/minute

process	product	specs	features	options
	<p>1700 Hinge Jamb Router</p> <p>Automatic hinge jamb routing up to 5 jams per minute</p>	<p>Hinge Specs 3" - 4-1/2"</p> <p>Jamb length 70" to 112"</p> <p>Jamb width 2-1/2" to 10-1/2"</p> <p>Jamb thickness 3/8" - 1-5/8"</p> <p>Electrical 115V @ 50 Amps</p> <p>Pneumatic 3 CFM @ 90 psi</p> <p>Floor Space req. (min.) 12' x 3'</p> <p>Approx. Shipping Wt 1100lbs</p> <p>Vacuum connection 4" duct</p>	<ul style="list-style-type: none"> • Quick change hinge locations • Accommodates a variety of jamb widths and lengths • Dual palm cycle start for safety • Dust collection ready for operator safety • Mortise hinges from 3" to 4-1/2" • Capable of mortising both 1/4" & 5/8" radius 	<ul style="list-style-type: none"> • 1200 CFM vacuum