

# MATERIAL SAFETY DATA SHEET

<b>Product:</b>	TM-2	<i>Note: The information herein is given in good faith. No warranty, expressed or implied, is made.</i>	
<b>Printed:</b>			
<b>Printed For:</b>			
<b>Original Issue Date:</b>	11/15/85	<b>Approved By:</b>	Chuck Hiddema
<b>Revision No. 5 Date:</b>	07/01/00		V.P. Technical Operations
<b>Section I - Identification</b>			
<b>Manufacturer:</b>	AGS Company		
<b>Street Address:</b>	2651 Hoyt St		
<b>City/State/Zip</b>	Muskegon Hts., MI 49444		
<b>Phone:</b>	800-253-0403		
<b>Phone:</b>	231-733-2101		
<b>FAX:</b>	231-733-1784		
<b>Transportation Emergency:</b>	CHEM-TEL		
<b>Phone:</b>	800-255-3924		
<b>Trade Name:</b>	Trim-Ease		
<b>Catalog No.:</b>	TM-2		
<b>Common Name:</b>	Trim-Ease		
<b>Container/Size:</b>			
<b>NFPA - Health:</b>	0		
<b>Flammability:</b>	1		
<b>Reactivity:</b>	0		
<b>Specific Hazard:</b>			
<b>HMIS - Health:</b>	0		
<b>Flammability:</b>	1		
<b>Reactivity:</b>	0		
<b>Protective Equipment:</b>	A		
<b>Section II - Hazardous Ingredients</b>			
<b>Hazardous Ingredient</b>	<b>CAS No.</b>	<b>Wgt. %</b>	<b>TLV</b>
1 Paraffin Wax	64742-51-4	30-45%	2 cu. M.
2 Petroleum Oil*	Not Assigned	30-45%	5 cu. M.
3 Naphthenic acid, zinc salt	12001-85-3	1-5%	
4			
5			
6			
7			
8			
9			
10			
<b>NOTES:</b>			
*Petroleum oil is severely hydrotreated or solvent refined. It does not require labeling as a carcinogen			

<b>Section III Physical Data</b>		Cat. No.	TM-2
pH - Supplied:	Not Determined		
pH - Diluted:	Not Determined		
Water Solubility:	Insoluble		
Specific Gravity:	(Water=1) 0.75		
Melting Point:	163 F. ASTM D127		
Boiling Point:	Not Determined		
% Volatiles:	Nil		
Vapor Pressure:	Negligible		
Vapor Density:	N/A		
Evaporation Rate:	N/A		
Appearance:	Tan waxy solid with bland petroleum odor.		
<b>Section IV Fire &amp; Explosion Data</b>			
Flash Point:	380 F		
Method:	C.O.C.		
Auto Ignition Temperature:	Not Determined		
Flammable Limits In Air	LEL: Not Determined		
	UEL: Not Determined		
Extinguishing Media:	Dry chemical, foam, carbon dioxide or water fog.		
Special Procedures:	Wear self-contained breathing apparatus. Use water fog to minimize vapors in air.		
Unusual Hazards:	None		
<b>Section V - Reactivity Data</b>			
Unstable and/or Auto Reactive:	Stable		
Incompatible Materials:	Strong Oxidizers		
Hazardous Decomposition Products:	Oxides of carbon and zinc.		
<b>Section VI - Emergency First Aid</b>			
Eyes:	Flush with water for at least 15 minutes. Consult a physician.		
Skin:	Wash with soap and water. Get medical attention if adverse effects arise.		
Ingestion:	Do not induce vomiting. Consult a physician.		
Inhalation:	Remove to fresh air. Administer oxygen or artificial respiration as needed.		
<b>Section VII - Health Effects</b>			
Eyes:	May cause discomfort.		
Skin:	In molten state may cause burn.		
Ingestion:	Not known.		
Inhalation:	Aspiration or inhalation of fumes or mist may cause respiratory problems.		
Other Effects:	Not known.		

<b>Section VIII - Ventilation and Protective Measures</b>		<b>Cat. No. TM-2</b>
<b>Ventilation Requirement:</b>	Local exhaust when using product in molten state.	
<b>Eyes:</b>	Yes	
<b>Gloves:</b>	Yes	
<b>Clothing:</b>	No	
<b>Respiratory:</b>	No	
<b>Other:</b>	Eye wash in work area.	
<b>Section IX - Storage and Handling Procedures</b>		
<b>Conditions to Avoid:</b>	Avoid excess heat and ignition sources	
<b>Section X - Spill Procedures and Waste Disposal</b>		
<b>Spill Procedure:</b>	Dike area to contain product spill. Allow to cool, scrape material up and place in container for disposal.	
<b>Disposal Method:</b>	Removal by an approved licensed waste hauler.	
<b>EPA Waste I.D. NO.:</b>	Non-Hazard	